

Access Track

The **Access Track** unit offers a simple method of providing discreet emergency lighting in areas that require a self-contained solution powered by an existing Global and Stucchi track system.

Supplied with a 'clip-in' symmetrical wide angle lens or asymmetrical 'corridor' lens for escape routes (both supplied) the **Access Track** luminaire simply connects to a permanent 230Volt supply via the integral track adapter to provide effective non-maintained emergency lighting with a 3hour duration.

Standard DALI/Self-Test

Incorporating tried and tested emergency driver technology from the ELP proSeries, the **Access Track** luminaire offers self-contained, non-maintained operation emergency lighting with integral automatic Self-Test.

Utilising appropriate Global or Stucchi track with DALI conductors and a DALI test system (such as the ELP SurePath system) the **Access Track** can provide central DALI testing.



SPECIFICATION

The **Access Track** can be specified for use with the Global or Stucchi track systems (standard or DALI). The enclosure houses an 'intelligent' proSeries LED driver/battery charger and a Lithium Iron Phosphate (LiFePO₄) battery. The integral downlight utilises a Nichia '3Watt' high power white LED operating in conjunction with a wide angle or 'corridor' distribution lens.

The **Access Track** polycarbonate housing is available finished in White or Black and the AccessTrack luminaire is mechanically locked onto the track.

Fully integrated components and the latest software ensure that the **Access Track** luminaire can be connected to any approved DALI control system.

When the mains supply is initially connected, the **Access Track** circuit initiates the Self-Test commissioning mode and then activates the weekly and annual test routine starting at random times to ensure tests do not get carried out simultaneously in the same areas. Faults such as charge failure, battery failure, etc. will be indicated locally by a bi-colour LED.

The **Access Track** luminaire will continually be prepared for a DALI signal even when operating in Self-Test mode. If a DALI signal is received the Self-Test mode will be disabled and the circuit will adopt full DALI mode.



Operation indicator LED shines through a skin in housing plastic



Emergency Lighting Products Limited
Parbrook House, Cillmans Industrial Estate,
Natts Lane Billingshurst, West Sussex RH14 9EZ

Telephone: +44 (0) 1403 786601
Fax: +44 (0) 1403 786602
e-mail: sales@elp.uk.com

Safe in the knowledge
elp.uk.com

Self-contained Track Mounted LED Downlight

Access Track

OPERATION	Subject	Plastic housing
Environmental	Protection against electric shock	Class II
	Ingress protection	IP40
	Rated operating ambient temperature	0°C to 40°C
Mains operation	Rated voltage supply	220/240V AC
	Mains frequency	50/60Hz
	Mains supply current	20mA
Emergency operation	Emergency duration	3 hours
	Battery recharge period	<24 hours
	Battery charging	Intelligent constant voltage
	Battery discharge current – nominal	370mA
	Lumen output	260 lumens (max)
Mechanical	Integral test routine	EN62034/DALI
	Dimensions (luminaire body)	142mm dia x 43mm (h)
	Dimensions (with track adapter)	142mm dia cut-out x 115mm (h)

ACCESS TRACK – Emergency Lighting Spacings

Mounting height Hm (m)	ACCESS/C		ACCESS/WIDE	
	Spacing (m) min 0.5Lux open area	Spacing (m) min 1Lux escape	Spacing (m) min 0.5Lux open area	Spacing (m) min 1Lux escape
2.0	n/a	14.0	13.9	12.8
2.5	n/a	15.3	15.1	14.0
3.0	n/a	16.5	14.8	13.6

ORDER CODES	Description
TRA/NM3/ST/WH/G	Access Track mounted luminaire, self-contained, Self-test, White – Global Track
TRA/NM3/ST/BK/G	Access Track mounted luminaire, self-contained, Self-test, Black – Global Track
TRA/NM3/D/WH/G	Access Track mounted luminaire, self-contained, Self-test, White – Global Track
TRA/NM3/D/BK/G	Access Track mounted luminaire, self-contained, Self-test, Black – Global Track
TRA/NM3/ST/WH/S	Access Track mounted luminaire, self-contained, Self-test, White – Stucchi Track
TRA/NM3/ST/BK/S	Access Track mounted luminaire, self-contained, Self-test, Black – Stucchi Track
TRA/NM3/D/WH/S	Access Track mounted luminaire, self-contained, DALI, White – Stucchi Track
TRA/NM3/D/BK/S	Access Track mounted luminaire, self-contained, DALI, Black – Stucchi Track

Emergency Lighting Products Limited
 Parbrook House, Cillmans Industrial Estate,
 Natts Lane Billingshurst, West Sussex RH14 9EZ

Telephone: +44 (0) 1403 786601
 Fax: +44 (0) 1403 786602
 e-mail: sales@elp.uk.com

Safe in the knowledge
elp.uk.com

